送测信息 Requester Information

委托人员 Requested by	韦品娥 亚太办公南部应用组	样品接收日期 Sample Received Date	Mar. 05, 2026
测试目的 Test Purpose	手板样机测试 Hand plate prototype test		
检验依据 Test Standard	JC/LAB-XSSY-003-2020 办公桌型式试验作业指导书		

样品信息 Sample Information

样品名称 Sample Name	样品型号 Model Number	样品描述 Sample Description	样品编号 Sample ID
高度升降桌 Height-adjustable Table	JC35TS-R142S-669-785-376-B-05-0-0-JC	配套电控：29V2A 墙插+M20C 手控一体 7A 过流保护程序。	HSK260187-01.01

测试结果 Test Result

样品编号 Sample ID	测试项目 Test Item	测试结果 Test Result	不符合项描述 Failure Description
HSK260187-01.01	见详细测试内容 See the test details	PASS	/

主检人员(Tested By): 严挺

测试日期(Testing Period): Mar. 09, 2026 - Apr. 07, 2026

审核及批准(Reviewed and approved by): 郭丹

发布日期（Issue date): Apr. 07, 2026

浙江捷昌线性驱动科技股份有限公司 检验检测专用章 检测中心

测试汇总 Test Summary

样品编号 Sample ID	测试项目 Test Item	测试结果 Test Result	不符合项描述 Failure Description
HSK260187-01.01	EN 527 寿命测试 Life test	PASS	/

备注(Remark):

1、N/A=not applicable 不适用；

2、N/T =not tested 未测试；

3、For information only 数据仅供参考

<table>
<tr><th>测试章节
Clause</th><th colspan="2">测试方法/要求
Test Procedure/Requirement</th></tr>
<tr><td>EN 527 寿命测试 Life test</td><td colspan="2">EN527 寿命 5000 次+均匀负载 5000 次

EN527 Life cycle testing + Even distributed loading 5000 cycles

前 5000 次按照 BS EN 527-2: 2106 标准测试：

The first 5000 cycles test according to BS EN 527-2: 2106:
<table>
<tr><th>重量位置 (Loading position)</th><th>次数(Cycles)</th></tr>
<tr><td>20kg 放在前面及边上 200mm 位置，其余负载放在中间
20kg at 200mm from the front and side edges, the remaining load put on the geometric center of the table top</td><td>1250</td></tr>
<tr><td>全部负载放在中间
All the loading put on the geometric center of the table top</td><td>2500</td></tr>
<tr><td>20kg 放在后面及边上 200mm 位置，其余负载放在中间
20kg at 200mm from the rear and side edges, the remaining load put on the geometric center of the table top</td><td>1250</td></tr>
</table>
完成 EN527 阶段寿命测试后，按额定负载均匀放置在桌面上，继续运行 5000 次，最低到最高，再返回最低算一个循环。
After EN527 life cycle testing, rated load even distributed on worktop continue to run an additional of 5000 cycles, from the lowest to highest, and then back to the lowest is one cycle.
额定负载：1000N Rated load:1000N

测试频率：运行 1 分钟，休息 2 分钟 Test frequency：Run 1 min，Rest 2 min</td></tr>
<tr><td>样品编号
Sample ID</td><td>测试结果
Test result</td><td>判定
Verdict</td></tr>
<tr><td>HSK260187-01.01</td><td>累计运行 10000 次，未出现异常。
It has been run 10000cycles in total without any abnormalities.</td><td>PASS</td></tr>
</table>

测试照片 Test photos

EN527 寿命测试 EN527 Life cycle durability testing ：

声明 Statement

1、本报告试验结果仅对受试样品有效；

The test results in this report are only valid for the tested samples;

2、未经许可本报告不得部分复制；

This report may not be partially reproduced without permission;

3、对本报告如有异议，请于收到报告之日起十五天内提出。

Objections to this report should be raised within 15 days from the date of receipt of the report.

报告结束 End of Report